

## Strain Relief Grip, Dust Tight, NPT1-1/4", Straight Male, Cable Range 0.94-1.25 in, Galvanized Steel

- For indoor use in wiring of enclosures, power boxes, machine tools, power centers and bus drop systems
- Prevents severe cable bending and pull-out
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Easy installation
- UL, CE certified



### Product Classification

Item Number	6008433
Part Number	-
Detail Description	Strain Relief Grip, Dust Tight, NPT1-1/4", Straight Male, Cable Range 0.94-1.25 in, Galvanized Steel

### Details

Cable Range	0.94-1.25 in   23.8-31.8 mm
Thread Size	NPT 1-1/4
Mesh Length	9.0in   228.6 mm
Approximate Break Strength	1100 lbs   498 kg
Mesh Material	Galvanized Steel
Ring Material	Aluminum Alloy

### Performance

Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2

### Packaging and Weights

UOM	1 pcs
Packaging	Bag
Weight, gross	0.99 lb   0.45 kg

### Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 30, 2024  
 Public

DATASHEET

CE

Compliant

UL

Compliant

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 30, 2024

Public