

Grounding Kit, Standard Type, 1/4"-5/8", 0.65 Meter

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Operation temperature -40~70 °C
- Waterproof IP68

**Product Classification**

Item Number	6008620
Part Number	-
Detail Description	Grounding kit, standard type, for 1/4"-5/8" cable, 0.65 meter, installation accessories included

General Specifications

Bonding Conductor Material	Copper
Bonding Conductor Wire Size	AWG 10
Braided Ground Strap Material	Copper, Tin-plated
Lug Type	One-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
Tape Material	PVC & Butyl

Dimensions

Bonding Conductor Length	0.65 m 25.6 in
Lug Hole Size	3/8"
Screw Size	3/8"x1/2"
Suitable Cable	1/4"-5/8"

Environmental Specifications

Operating Temperature	-40°C to +70 °C (-40 °F to +158 °F)
Weatherproofing Method	Butyl and electric tape

Electrical Specifications

Contact Transition Resistance	Maximum 10mΩ
-------------------------------	--------------

Packaging and Weights

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Sep 26, 2024
 Public

Height, Packed	320 mm 12.60 in
Width, Packed	220 mm 8.66 in
Included	Grounding kit Hardware Lug Two roll of PVC tape One roll of butyl rubber tape Zip tie Silicone grease
UOM	Kit
Packaging	Bag
Weight, Gross	0.507 kg 1.118 lbs
Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

