

Strain Relief Grip, Deluxe Cord,M40,Straight Male,Cable Range 1.00-1.125 in, SS304, Black

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- The color design fits the color of the equipment better
- UL, CE certified



Product Classification	
Item Number	6008659
Part Number	-
Detail Description	Strain Relief Grip, Deluxe Cord,M40,Straight Male,Cable Range 1.00-1.125 in,SS304,Black
Details	
Cable Range	1.00-1.125 in 25.4-28.6 mm
Thread Size	M40*1.5
Mesh Length	10.0 in 254.0 mm
Approximate Break Strength	1100 lbs 498 kg
Mesh Material	Stainless Steel with Black Nylon
Ring Material	Aluminum Alloy
Performance	
Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting
Packaging and Weights	
UOM	1 pcs
Packaging	Bag
Weight, gross	0.48 lb 0.22 kg

Certifications and Compliance

For more information, please visit: www.maxdao.com

 \bowtie

lin

©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 30, 2024 Public

DATASHEET



ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
CE	Compliant
UL	Compliant

For more information, please visit: www.maxdao.com



©Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 30, 2024 Public