

Waveguide Cable Clamp, Rubber Lining Hole 25x15mm, For R140 Waveguide

- Easy and quick installation
- Robust design & material
- Universal fixing design on bracket, angle steel
- Operation Temperature -40~85 °C
- RoHS certified



Product Classification

Item Number	6001258
Part Number	-
Detail Description	Waveguide cable clamp, rubber lining hole 25x15mm, for R140 Waveguide

General Specifications

Metal Parts Material	Stainless steel 304
Rubber Material	EPDM
Rubber Color	Black
Mounting Plate Thickness	3-25mm
Waveguide Size	R140

Dimensions

Threaded Rod Length	400 mm 15.75 in
Adapter Width	24 mm 0.94 in
Rubber Lining Hole	25x15 mm 0.98x0.59 in

Environmental Specifications

Operating Temperature	-40 °C to +85 °C (-40 °F to +185 °F)
Corrosion Resistance	≥720 hours in salt spray chamber, base on IEC 60068-2-11
UV Resistance	≥72 hours, base on ISO4892.3-1994

Packaging and Weights

Height, Packed	600 mm 23.62 in
Width, Packed	200 mm 7.87 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.332 kg 0.732 lbs

Certifications and Compliance

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Sep 13, 2024

Public

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Sep 13, 2024

Public