

Grounding Kit, Universal Type, 1/4"-1-5/8", 0.5 Meter

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Operation Temperature -40~70 °C
- Waterproof IP68



Product Classification

| | |
|--------------------|--|
| Item Number | 6003350 |
| Part Number | - |
| Detail Description | Grounding Kit, tinned GST type, for 1/4"-1-5/8" cable, 0.5 meter, installation accessories including |

General Specifications

| | |
|-----------------------------|--------------------|
| Bonding Conductor Material | Copper |
| Bonding Conductor Wire Size | AWG 6 |
| Grounding Strap Material | Copper, Tin Plated |
| Lug Type | One-hole lug |
| Screw Material | Stainless Steel |
| Flat washer Material | Stainless Steel |
| Spring washer Material | Stainless Steel |
| Nut Material | Stainless Steel |
| PVC tape Material | PVC |
| Butyl Rubber Tape Material | Butyl |

Dimensions

| | |
|--------------------------|-----------------|
| Bonding Conductor Length | 0.5 m 19.7 in |
| Lug Hole Size | M8 |
| Screw Size | M8 X 25 mm |
| Suitable Cable | 1/4" - 1-5/8" |

Environmental Specifications

| | |
|------------------------|-------------------------------------|
| Operating Temperature | -40°C to +70 °C (-40 °F to +158 °F) |
| Weatherproofing Method | Butyl and electric tape |

Electrical Specifications

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Nov 19, 2024
 Public

| | |
|-------------------------------|--------------|
| Contact Transition Resistance | Maximum 10mΩ |
|-------------------------------|--------------|

Packaging and Weights

| | |
|----------------|-------------------|
| Height, Packed | 320 mm 12.60 in |
|----------------|-------------------|

| | |
|---------------|------------------|
| Width, Packed | 220 mm 8.66 in |
|---------------|------------------|

| | |
|----------|--|
| Included | Grounding kit Hardware Lug One roll of PVC tape One roll of butyl rubber tape |
|----------|--|

| | |
|-----|-----|
| UOM | Kit |
|-----|-----|

| | |
|-----------|-----|
| Packaging | Bag |
|-----------|-----|

| | |
|---------------|---------------------|
| Weight, Gross | 0.23 kg 0.507 lbs |
|---------------|---------------------|

Certifications and Compliance

| | |
|---------------|---|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
|---------------|---|

| | |
|------|-----------|
| RoHS | Compliant |
|------|-----------|

