

## Pulling grip with integral pulling eye 6.0-9.0mm, Galvanized Steel

- Used in industrial plants, commercial buildings, utility work and light duty underground transmission line stringing
- The integral pulling eye can be attached to the tow rope
- Convenient, high strength pulling tool
- Easily attach to a swivel
- Easily installed and removed.
- CE certified




---

### Product Classification

|                    |  |
|--------------------|--|
| Item Number        | 6008754  |
| Part Number        | -  |
| Detail Description | Pulling grip with integral pulling eye 6.0-9.0mm, Galvanized Steel |

### Details

|                            |                                    |
|----------------------------|------------------------------------|
| Cable Range                | 0.24-0.36 in   6.0-9.0 mm          |
| Mesh Length                | 8.5 in   215.9 mm                  |
| Eye Length                 | 2.0 in   50.8 mm                   |
| Approximate Break Strength | 661 lbs   300 kg                   |
| Working Load               | 132 lbs   60 kg (Safety Factor 5*) |
| Mesh Material              | Galvanized Steel                   |

### Packaging and Weights

|               |                   |
|---------------|-------------------|
| UOM           | 1 pcs             |
| Packaging     | Bag               |
| Weight, gross | 0.13 lb   0.06 kg |

### Certifications and Compliance

|               |  |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS          | Compliant  |
| CE            | Compliant  |

