

Hoisting Grip, Pre-Laced, for 3.00-3.49 in Cable

- Hoisting grips are used with safety ropes to safely lift cables onto the tower and providing permanent support
- Used for support to absorb additional strain from vibration, expansion, contraction and flexing.
- The pre-laced is used when top connector is installed after the antenna transmission line is hoisted.
- Stainless steel wire mesh is for indoor or outdoor use.
- CE certified



Product Classification

Item Number	6008795
Part Number	-
Detail Description	Hoisting Grip, Pre-Laced, for 3.00-3.49 in Cable

Details

Cable Range	3.00-3.49 in 76.2-88.6 mm
Mesh Length	26.0 in 660.4 mm
Eye Length	21.0 in 533.4mm
Maximum Spacing Intervals	200 ft 60.96 m
Approximate Break Strength	7300 lbs 3311 kg
Working Load	1460 lbs 662 kg (Safety Factor 5*)
Mesh Material	Stainless Steel
Warning Label	Yellow Mylar

Packaging and Weights

UOM	1 pcs
Packaging	Bag
Weight, gross	1.15 lb 0.52 kg

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
CE	Compliant