MAXDAO

Grounding Kit, Clip-on Type, 7/8", 1.5 Meter, With Two 3/8" Hole Lug

- **Easy and quick installation**
- **Low contact transition resistance of maximum 10mΩ**
- **Operation temperature -40~70 ℃**
- **Waterproof IP68**

Product Classification

Item Number	6008836
Part Number	-
Detail Description	Grounding kit, clip-on type, for 7/8" cable, cable length 1.5m, installation accessories and installation guide included

General Specifications

Bonding Conductor Material	Copper
Bonding Conductor Wire Size	6 AWG
Grounding Strap Material	Copper
Lug Type	Two-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
Tape Material	PVC & Butyl

Dimensions

Bonding Conductor Length	1.5 m	5 feet
Lug Hole Size	3/8"
Screw Size	3/8"x1"
Suitable Cable	7/8"

Environmental Specifications

Operating Temperature	-40°C to +70 °C (-40 °F to +158 °F)
Weatherproofing Method	Butyl and electric tape

Electrical Specifications

Contact Transition Resistance	Maximum 10mΩ

Packaging and Weights

Height, Packed	320 mm | 12.60 in
Width, Packed	220 mm | 8.66 in
Included	Grounding kit | Hardware | Lug | One roll of PVC tape | One roll of butyl rubber tape | One installation guide
UOM	Kit
Packaging	Bag
Weight, Gross	0.535 kg | 1.18 lbs

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

For more information, please visit:
www.maxdao.com