

## Grounding Kit, Clip-on Type, 1/2", 1.5 Meter, With Two 3/8" Hole Lug

- Easy and quick installation
- Low contact transition resistance of maximum
- Operation temperature -40~70 °C
- Waterproof IP68



| Product Classification        |   |  |
|-------------------------------|---|--|
| Item Number                   | 6008837   |  |
| Part Number                   | -   |  |
| Detail Description            | Grounding kit, clip-on type, for 1/2" cable, cable length 1.5m installation accessories and installation guide included |  |
| General Specifications        |   |  |
| Bonding Conductor Material    | Copper  |  |
| Bonding Conductor Wire Size   | 6 AWG   |  |
| Grounding Strap Material      | Copper  |  |
| Lug Type                      | Two-hole lug  |  |
| Screw Material                | Stainless Steel   |  |
| Flat washer Material          | Stainless Steel   |  |
| Spring washer Material        | Stainless Steel   |  |
| Nut Material                  | Stainless Steel   |  |
| Tape Material                 | PVC & Butyl   |  |
| Dimensions                    |   |  |
| Bonding Conductor Length      | 1.5 m   5 feet  |  |
| Lug Hole Size                 | 3/8"  |  |
| Screw Size                    | 3/8"x1"   |  |
| Suitable Cable                | 1/2"  |  |
| Environmental Specifications  |   |  |
| Operating Temperature         | -40°C to +70 °C (-40 °F to +158 °F)   |  |
| Weatherproofing Method        | Butyl and electric tape   |  |
| Electrical Specifications     |   |  |
| Contact Transition Resistance | Maximum 10mΩ  |  |
| Packaging and Weights         |   |  |

For more information, please visit:

www.maxdao.com



| Height, Packed                | 320 mm   12.60 in   |
|-------------------------------|---|
| Width, Packed                 | 220 mm   8.66 in  |
| Included                      | Grounding kit   Hardware   Lug   One roll of PVC tape  <br>One roll of butyl rubber tape   One installation guide |
| UOM                           | Kit   |
| Packaging                     | Bag   |
| Weight, Gross                 | 0.53 kg   1.17 lbs  |
| Certifications and Compliance |   |
| ISO 9001:2015                 | Designed, manufactured and/or distributed under this quality management system                                    |
| RoHS                          | Compliant   |



www.maxdao.com

For more information, please visit: