

Strain Relief Grip, Deluxe Cord,NPT 2,Straight Male,Cable Range 1.125-1.250 in, SS304

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL, CE certified



Product Classification

| | |
|--------------------|---|
| Item Number | 6009104 |
| Part Number | - |
| Detail Description | Strain Relief Grip, Deluxe Cord,NPT 2,Straight Male,Cable Range 1.125-1.250 in, SS304 |

Details

| | |
|----------------------------|---------------------------------|
| Cable Range | 1.125-1.250 in 28.58-31.75 mm |
| Thread Size | NPT 2 |
| Mesh Length | 10.0 in 254.0 mm |
| Approximate Break Strength | 1100 lbs 499 kg |
| Mesh Material | Stainless Steel |
| Ring Material | Aluminum Alloy |

Performance

| | |
|------------------------|--|
| Flammability | UL 94HB & UL 94V-2 |
| Hazardous Locations | Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 |
| Operating Temperatures | -34 °C to +115 °C (-30 °F to +240 °F) |
| Wet Locations | Suitable for use in wet locations when used with a listed sealing ring between box and fitting |

Packaging and Weights

| | |
|---------------|-------------------|
| UOM | 1 pcs |
| Packaging | Bag |
| Weight, gross | 1.10 lb 0.50 kg |

Certifications and Compliance

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 30, 2024

Public

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

RoHS

Compliant

CE

Compliant

UL

Compliant

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 30, 2024

Public