

In Line Fiber Splice Enclosure, For 4in4out Fiber Optic

- Easy and quick installation
- Wide capability range
- Various choice based on fiber counts
- Mounted on wall or aerial hanger
- Waterproof IP68



Product Classification

Item Number	TBD12
Part Number	-
Detail Description	In line fiber splice enclosure, for 4in4out fiber optic

General Specifications

Box Material	PC
Color	Black
Max Splice Capacity	144 Core Fiber
Number Of Trays	6
Number of Cable Ports	4 in 4 out

Dimensions

Height	110 mm 4.33 in
Width	190 mm 7.48 in
Length	430 mm 16.93 in
Input Cable 1 Outer Diameter	16 mm 0.63 in
Input Cable 2 Outer Diameter	20 mm 0.78 in
Output Cable 1 Outer Diameter	16 mm 0.63 in
Output Cable 2 Outer Diameter	20 mm 0.78 in

Environmental Specifications

Operating Temperature	-40 °C to +70 °C (-40 °F to +158 °F)
-----------------------	--------------------------------------

Packaging and Weights

Height, Packed	130 mm 5.12 in
Width, Packed	220 mm 8.66 in
Length, Packed	480 mm 18.89 in
Included	Mounting kits

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Nov 21, 2024
 Public

UOM	Pcs
-----	-----

Packaging	Carton
-----------	--------

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
---------------	--

RoHS	Compliant
------	-----------

