

Dome Fiber Splice Enclosure, For 1in6out Fiber Optic

- Easy and quick installation
- Used to distribute, splice, and store the outdoor optical cables
- Applicable to overhead, man-well of pipeline, embedded situation
- Various choice based on fiber counts
- Mount on pipe or aerial hanger
- Waterproof IP68



Product Classification

Item Number	TBD13
Part Number	-
Detail Description	Dome fiber splice enclosure, for 1in6out fiber optic

General Specifications

Box Material	PP
Color	Black
Max Splice Capacity	288 Core Fiber
Number Of Trays	6
Number of Cable Ports	1 in 6 out
Structure Type	Heat Shrinkable Sealing

Dimensions

Height	205 mm 8.07 in
Outer Diameter	470 mm 18.5 in
Input Cable Outer Diameter	65 mm 2.56 in
Output Cable Outer Diameter	21 mm 0.83 in

Environmental Specifications

Operating Temperature	-40 °C to +60 °C (-40 °F to +140 °F)
-----------------------	--------------------------------------

Packaging and Weights

Height, Packed	220 mm 8.66 in
Width, Packed	500 mm 19.68 in
Length, Packed	500 mm 19.68 in
Included	Mounting kits
UOM	Pcs
Packaging	Carton

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Nov 21, 2024

Public

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

