MAXDAO

Outer FTTH Box, For 24Core Fiber Optic

- **Easy and quick installation**
- **Used to distribute, splice, and store the outdoor optical cables**
- **Various choice based on fiber counts**
- **Mount on wall, pipe or aerial hanger**
- **Waterproof IP65**

Product Classification

Item Number	TBD15
Part Number	-
Detail Description	Outer FTTH box, for 24Core fiber optic

General Specifications

Box Material	PC+ABS
Color	Grey
Max Splice Capacity	24 Core Fiber
Number Of Trays	4
Number of Cable Ports	1 in 24 out
Adapter Type	SC Simplex

Dimensions

Height	105 mm | 4.13 in
Width	220 mm | 8.66 in
Length	340 mm | 13.38 in
Input Cable Outer Diameter	10-17.5 mm | 0.39-0.69 in
Output Cable Outer Diameter	7 mm | 0.27 in

Environmental Specifications

Operating Temperature	-40 °C to +65 °C (-40 °F to +149 °F)

Packaging and Weights

Height, Packed	220 mm | 8.66 in
Width, Packed	500 mm | 19.68 in
Length, Packed	500 mm | 19.68 in
Included	Mounting kits
UOM	Pcs
Packaging	Carton

MAXDAO

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant