

Outer FTTH Box, For 12Core Fiber Optic

- Easy and quick installation
- Used to distribute, splice, and store the outdoor optical cables
- Various choice based on fiber counts
- 1 oval optical cable entry, and 8 pre-connected adapters
- Mount on wall, pipe or aerial hanger
- Waterproof IP68



Product Classification

| | |
|--------------------|--|
| Item Number | TBD16 |
| Part Number | - |
| Detail Description | Outer FTTH box, for 12Core fiber optic |

General Specifications

| | |
|-----------------------|---------------|
| Box Material | PC+ABS |
| Color | Black |
| Max Splice Capacity | 12 Core Fiber |
| Number of Cable Ports | 1 in 8 out |
| Adapter Type | SC Simplex |

Dimensions

| | |
|-----------------------------|-------------------|
| Height | 82 mm 3.23 in |
| Width | 182 mm 7.16 in |
| Length | 280 mm 11.02 in |
| Input Cable Outer Diameter | 13 mm 0.51 in |
| Output Cable Outer Diameter | 7 mm 0.27 in |

Environmental Specifications

| | |
|-----------------------|--------------------------------------|
| Operating Temperature | -40 °C to +65 °C (-40 °F to +149 °F) |
|-----------------------|--------------------------------------|

Packaging and Weights

| | |
|----------------|-------------------|
| Height, Packed | 101 mm 4.0 in |
| Width, Packed | 254 mm 10.0 in |
| Length, Packed | 300 mm 11.81 in |
| Included | Mounting kits |
| UOM | Pcs |
| Packaging | Carton |

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Nov 21, 2024
 Public

Certifications and Compliance

| | |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |

