

Strain Relief Grip, Deluxe Cord,M32,Straight Male,Cable Range 0.625-0.750 in,

SS304, Black

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- The color design fits the color of the equipment better
- UL, CE certified



| Product Classification | |
|----------------------------|---|
| Item Number | 6009251 |
| Part Number | - |
| Detail Description | Strain Relief Grip, Deluxe Cord,M32,Straight Male,Cable Range 0.625-0.750 in,SS304,Black |
| Details | |
| Cable Range | 0.500-0.625 in 16.0-19.1 mm |
| Thread Size | M32*1.5 |
| Mesh Length | 8.9 in 226.1 mm |
| Approximate Break Strength | 450 lbs 204 kg |
| Mesh Material | Stainless Steel with Black Nylon |
| Ring Material | Aluminum Alloy |
| Performance | |
| Flammability | UL 94HB & UL 94V-2 |
| Hazardous Locations | Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 |
| Operating Temperatures | -34 °C to +115 °C (-30 °F to +240 °F) |
| Wet Locations | Suitable for use in wet locations when used with a listed sealing ring between box and fitting |
| Packaging and Weights | |
| UOM | 1 pcs |
| Packaging | Bag |
| Weight, gross | 0.44 lb 0.20 kg |

Certifications and Compliance

For more information, please visit: www.maxdao.com

 \bowtie

in

©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 30, 2024 Public DATASHEET



| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
|---------------|--|
| RoHS | Compliant |
| CE | Compliant |
| UL | Compliant |

For more information, please visit: www.maxdao.com



©Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Aug 30, 2024 Public