

Freestanding Cabinet, 600x400x1600mm

- Easy assembly makes system operation very simple
- Stand-alone electric cabinet, inapplicable for cabinet incorporation
- High door plate (approx 25mm from the ground) to ensure smooth door opening
- Steady structure with 480Kg static load
- Unique main body frame integrally welded with 5-fold sections ensures high strength and IP55 of cabinet body
- Module holes densely distributed at 25mm spacing on the frame guarantee the flexibility and universality of installation
- The mounting plate can be pushed into the cabinet by plastic slide through rail



| Product Classification | |
|------------------------------|--------------------------------------|
| Item Number | TBD21 |
| Part Number | - |
| Detail Description | Freestanding cabinet, 600x400x1600mm |
| General Specifications | |
| Material | Cold rolled steel sheet |
| Finish | Electrostatic Spraying |
| Color | Grey |
| Weight Capacity - Stationary | 480 Kg |
| Dimensions | |
| Height | 1600 mm 62.99 in |
| Depth | 400 mm 15.75 in |
| Width | 600 mm 23.62 in |
| Environmental Specifications | |
| Operating Temperature | -25 °C to +55 °C (-13 °F to +131 °F) |
| Waterproof | IP55, base on IEC60529 |
| Packaging and Weights | |
| Height, Packed | 100 mm 3.94 in |
| Width, Packed | 810 mm 31.89 in |









| Length, Packed | 2020 mm 79.53 in |
|-------------------------------|--|
| UOM | Pcs |
| Packaging | Carton |
| Weight, Gross | 85 kg 187 lbs |
| Certifications and Compliance | |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |

