ATF# ITM0401 VFRSION A/8 DATE 08/20/203



Acetal Cable Tie, 1/2"x16", Black

- Weatherproof acetal strap body and head provides excellent ultraviolet light and chemical resistance
- Double stainless steel locking barbs
- Ideal for securing cables in outdoor applications and vertical ladder racks
- Meets Telcordia TR-TSY-000789



Acetal Specifications erial Aceta king Barb Material Stain or Black nensions th 12.5 gth 406.4 kness 1.5 m imum Bundle Diameter 101.6	313 al cable tie, 1/2 in X 16in
Aceta Interal Specifications Interal Specifications Interal Specifications Interal Specifications Interal Specifications Interal Stain Interal Specifications In	al cable tie, 1/2 in X 16in
erial Aceta Aceta Ling Barb Material Stain Black Bensions th 12.5 gth 406.4 kness 1.5 m imum Bundle Diameter 101.6	al cable tie, 1/2 in X 16in
Aceta king Barb Material Stain Black nensions th 12.5 gth 406.4 kness 1.5 m imum Bundle Diameter 101.6	
Stain Black steers Black steers been since Black steers been steer	
Black th 12.5 gth 406.4 kness 1.5 n imum Bundle Diameter 101.6	al
th 12.5 gth 406.4 kness 1.5 n imum Bundle Diameter 101.6	less steel 304
th 12.5 gth 406.4 kness 1.5 n imum Bundle Diameter 101.6	
kness 1.5 n imum Bundle Diameter 101.6	
kness 1.5 n imum Bundle Diameter 101.6	mm 0.49 in
imum Bundle Diameter 101.6	l mm 16 in
	nm 0.06 in
	5 mm 4 in
chanical Specifications	
mum loop Tensile Strength 1112	N 250 lbs
ironmental Specifications	
rating Temperature -40 °	C to +85 °C (-40 °F to +185 °F)
nmability UL94	НВ
Resistance ≥10	00 hours, base on ISO4892.3-1994
kaging and Weights	
ht, Packed 120 r	nm 4.72 in
th, Packed 450 r	nm 17.72 in
// Kit o	
kaging Bag	50
ght, Gross 0.71	50

Certifications and Compliance







ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
TR-TSY-000789	Qualified

