

Hoisting Grip, Pre-Laced, for 0.94-1.08 in Cable

- Hoisting grips are used with safety ropes to safely lift cables onto the tower and providing permanent support
- Used for support to absorb additional strain from vibration, expansion, contraction and flexing.
- The pre-laced is used when top connector is installed after the antenna transmission line is hoisted.
- Stainless steel wire mesh is for indoor or outdoor use.
- CE certified



Product Classification

Item Number	6009273
Part Number	-
Detail Description	Hoisting Grip, Pre-Laced, for 0.94-1.08 in Cable

Details

Cable Range	0.94-1.08 in 23.9-27.4 mm
Mesh Length	17.0 in 431.8 mm
Eye Length	13.0 in 330.2mm
Maximum Spacing Intervals	200 ft 60.96 m
Approximate Break Strength	3000 lbs 1360 kg
Working Load	600 lbs 272 kg (Safety Factor 5*)
Mesh Material	Stainless Steel
Warning Label	Yellow Mylar

Packaging and Weights

UOM	1 pcs
Packaging	Bag
Weight, gross	0.38 lb 0.17 kg

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
CE	Compliant