

## Strain Relief Grip, Dust Tight, NPT 1/2", Non-Insulated, Cable Range 0.30-0.43"

- For indoor use in wiring of enclosures, power boxes, • machine tools, power centers and bus drop systems
- Prevents severe cable bending and pull-out •
- Helps eliminate direct tension from terminals and • remove strain from critical electrical connection
- **Easy installation** •
- UL, CE certified •



Classification	
Material Number	6002077
Part Number	DTG1202
Status	Active
Detail Description	Strain relief grip, dust tight, NPT 1/2", cable range 0.30-0.43", with lock nut
Details	
Cable Range	0.30-0.43 in   7.62 -10.92 mm
Thread Size	NPT 1/2"
Mesh Length	4.5 in   114.3 mm
Approx. Break Strength	300 lbs   136.1 kg
Mesh Material	Galvanized Steel
Body Material	Aluminum
Performance	
Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Package	
Packaging Quantity	1 kit
Weight, gross	0.057 lb   0.026 kg
Certifications	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant
CE	Compliant

Page 1 of 1

For more information, please visit: www.maxdao.com

## ©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Mar 10, 2023



Public