

Strain Relief Grip, Dust Tight, NPT 1/2", Non-Insulated, Cable Range 0.22-0.32"

- For indoor use in wiring of enclosures, power boxes, machine tools, power centers and bus drop systems
- Prevents severe cable bending and pull-out
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Easy installation
- UL, CE certified



Classification

Material Number	6002096
Part Number	DTG1201
Status	Active
Detail Description	Strain relief grip, dust tight, NPT 1/2", cable range 0.22-0.32", with lock nut

Details

Cable Range	0.22-0.32 in 5.58 -8.13 mm
Thread Size	NPT 1/2"
Mesh Length	4.0 in 101.6 mm
Approx. Break Strength	300 lbs 136.1 kg
Mesh Material	Galvanized Steel
Body Material	Aluminum

Performance

Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2

Package

Packaging Quantity	1 kit
Weight, gross	0.044 lb 0.02 kg

Certifications

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant
CE	Compliant