

Strain Relief Grip, Deluxe Cord, NPT 1/2", 90°Male, Cable Range 0.375-0.500" -

- For use in indoor & outdoor applications to • prevent cable pull-out, control arc of bend, and to provide a tight seal against environmental elements such as dirt, moisture and coolants.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- **UL, CE certified** .

Classification	
Material Code	6002955
Part Number	DCG9408
Status	Active
Detail Description	Strain relief grip, deluxe cord, NPT 1/2", 90° male, cable range 0.375-0.500"
Details	
Cable Range	0.375-0.500 in 9.52-12.70 mm
Thread Size	NPT 1/2"
Mesh Length	6.0 in 152.4 mm
Mesh Material	Stainless Steel
Body Material	Aluminum
Performance	
Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2 Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting
Package	
Packaging Quantity	1 pcs
Weight, gross	0.11 lb 0.05 kg
Certifications	
ICO 0001-2015	Designed, manufactured and/or distributed under this

Designed, manufactured and/or distributed under this quality management system

For more information, please visit: www.maxdao.com

©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 21, 2023 Public

Page 1 of 2

DATASHEET

RoHS	Compliant
UL	Compliant
CE	Compliant

Page 2 of 2

For more information, please visit: www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 21, 2023

Public

MAXDAO