

Strain Relief Grip, Deluxe Cord, NPT 2", Straight Male, Cable Range 1.562-1.687"

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL, CE certified



Classification

Material Code	6003481
Part Number	DCG1627
Status	Active
Detail Description	Strain relief grip, deluxe cord, NPT 2", straight male, cable range 1.562-1.687"

Details

Cable Range	1.562-1.687 in 39.67 -42.85 mm
Thread Size	NPT 2"
Mesh Length	15.0 in 381.0 mm
Mesh Material	Stainless Steel
Body Material	Aluminum

Performance

Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting

Package

Packaging Quantity	1 pcs
Weight, gross	0.944 lb 0.428 kg

Certifications

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

UL

Compliant

CE

Compliant

