

**Strain Relief Grip, Deluxe Cord, NPT 2-1/2", Straight Male, Cable Range 1.812-1.937"**

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL, CE certified

**Classification**

|                    |                                                                                      |
|--------------------|--------------------------------------------------------------------------------------|
| Material Code      | 6003597                                                                              |
| Part Number        | DCG2031                                                                              |
| Status             | Active                                                                               |
| Detail Description | Strain relief grip, deluxe cord, NPT 2-1/2", straight male, cable range 1.812-1.937" |

**Details**

|               |                                  |
|---------------|----------------------------------|
| Cable Range   | 1.812-1.937 in   46.02 -49.20 mm |
| Thread Size   | NPT 2-1/2"                       |
| Mesh Length   | 15.0 in   381.0 mm               |
| Mesh Material | Stainless Steel                  |
| Body Material | Aluminum                         |

**Performance**

|                        |                                                                                                              |
|------------------------|--------------------------------------------------------------------------------------------------------------|
| Flammability           | UL 94HB & UL 94V-2                                                                                           |
| Hazardous Locations    | Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 |
| Operating Temperatures | -34 °C to +115 °C (-30 °F to +240 °F)                                                                        |
| Wet Locations          | Suitable for use in wet locations when used with a listed sealing ring between box and fitting               |

**Package**

|                    |                     |
|--------------------|---------------------|
| Packaging Quantity | 1 pcs               |
| Weight, gross      | 2.059 lb   0.934 kg |

**Certifications**

|               |                                                                                |
|---------------|--------------------------------------------------------------------------------|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS          | Compliant                                                                      |
| UL            | Compliant                                                                      |

