

Strain Relief Grip, Deluxe Cord, NPT 3", Straight Male, Cable Range 2.437-2.625"

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL, CE certified

**Classification**

| | |
|--------------------|--|
| Material Code | 6003600 |
| Part Number | DCG2442 |
| Status | Active |
| Detail Description | Strain relief grip, deluxe cord, NPT 3", straight male, cable range 2.437-2.625" |

Details

| | |
|---------------|----------------------------------|
| Cable Range | 2.437-2.625 in 61.90 -66.68 mm |
| Thread Size | NPT 3" |
| Mesh Length | 18.0 in 457.2 mm |
| Mesh Material | Stainless Steel |
| Body Material | Aluminum |

Performance

| | |
|------------------------|--|
| Flammability | UL 94HB & UL 94V-2 |
| Hazardous Locations | Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2 |
| Operating Temperatures | -34 °C to +115 °C (-30 °F to +240 °F) |
| Wet Locations | Suitable for use in wet locations when used with a listed sealing ring between box and fitting |

Package

| | |
|--------------------|---------------------|
| Packaging Quantity | 1 pcs |
| Weight, gross | 2.707 lb 1.228 kg |

Certifications

| | |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |
| UL | Compliant |

