

**Strain Relief Grip, Deluxe Cord, NPT 3", Straight Male, Cable Range 2.812-3.000"**

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL, CE certified

**Classification**

Material Code	6003602
Part Number	DCG2448
Status	Active
Detail Description	Strain relief grip, deluxe cord, NPT 3", straight male, cable range 2.812-3.000"

**Details**

Cable Range	2.812-3.000 in   71.42 -76.20 mm
Thread Size	NPT 3"
Mesh Length	19.0 in   482.6 mm
Mesh Material	Stainless Steel
Body Material	Aluminum

**Performance**

Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting

**Package**

Packaging Quantity	1 pcs
Weight, gross	2.723 lb   1.235 kg

**Certifications**

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant

