

Strain Relief Grip, Dust Tight, NPT 3/4", Insulated, Stainless Steel ,Cable Range

0.52-0.73"

- For indoor and outdoor use in wiring of enclosures, power boxes, machine tools, power centers and bus drop systems
- Prevents severe cable bending and pull-out
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Easy installation
- UL, CE certified



Classification	
Material Number	6004423
Part Number	DTG3401
Status	Active
Detail Description	Strain relief grip, dust tight, NPT 3/4", Stainless Steel, cable range 0.52-0.73", with lock nut and Insulating bushing
Details	
Cable Range	0.52-0.73 in 13.21 -18.54 mm
Thread Size	NPT 3/4"
Mesh Length	6.5 in 165.1 mm
Approx. Break Strength	450 lbs 204.1 kg
Mesh Material	Stainless Steel
Body Material	Aluminum
Performance	
Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Package	
Packaging Quantity	1 kit
Weight, gross	0.119 lb 0.054 kg
Certifications	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant
CE	Compliant

For more information, please visit: www.maxdao.com

 \bowtie

in

©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Mar 10, 2023 Public Page 1 of 1