

Strain Relief Grip, Deluxe Cord, NPT 1/2", 90°Male, Cable Range 0.187-0.250"

- For use in indoor & outdoor applications to prevent cable pull-out, control arc of bend, and to provide a tight seal against environmental elements such as dirt, moisture and coolants.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- **UL, CE certified**



Classification	
Material Code	6004432
Part Number	DCG9404
Status	Active
Detail Description	Strain relief grip, deluxe cord, NPT 1/2", 90 $^\circ$ male, cable range 0.187-0.250"
Details	
Cable Range	0.187-0.250 in 4.75-6.35 mm
Thread Size	NPT 1/2"
Mesh Length	4.25 in 107.8 mm
Mesh Material	Stainless Steel
Body Material	Aluminum
Performance	
Flammability	UL 94HB & UL 94V-2 (Fitting)
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2 Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting
Package	
Packaging Quantity	1 pcs
Weight, gross	0.101 lb 0.046 kg
Certifications	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

For more information, please visit: www.maxdao.com





DATASHEET



RoHS Compliant

UL Compliant

CE Compliant

