

Strain Relief Grip, Deluxe Cord, NPT 1", Straight Male, Cable Range 1.125-1.250"

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL, CE certified



Classification

Material Code	6004437
Part Number	DCG820
Status	Active
Detail Description	Strain relief grip, deluxe cord, NPT 1", straight male, cable range 1.125-1.250"

Details

Cable Range	1.125-1.250 in 28.58 -31.75 mm
Thread Size	NPT 1"
Mesh Length	10.0 in 254.0 mm
Mesh Material	Stainless Steel
Body Material	Aluminum

Performance

Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting

Package

Packaging Quantity	1 pcs
Weight, gross	0.496 lb 0.225 kg

Certifications

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
---------------	--

DATASHEET

RoHS	Compliant
UL	Compliant
CE	Compliant

