Strain Relief Grip, Deluxe Cord, NPT 2-1/2", Straight Male, Cable Range 1.687-1.812"

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- **UL, CE certified**



Classification	
Part Number	DCG2029
Status	Active
Detail Description	Strain relief grip, deluxe cord, NPT 2-1/2", straight male, cable range 1.687-1.812"
Details	
Cable Range	1.687-1.812 in 42.85 -46.02 mm
Thread Size	NPT 2-1/2"
Mesh Length	15.0 in 381.0 mm
Mesh Material	Stainless Steel
Body Material	Aluminum
Performance	
Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting
Package	
Packaging Quantity	1 pcs
Weight, gross	2.050 lb 0.93 kg
Certifications	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant



CE Compliant



