

## Strain Relief Grip, Deluxe Cord, NPT 3", Straight Male, Cable Range 1.687-1.812"

- For indoor and outdoor where cables or wires are • exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and • remove strain from critical electrical connection
- Multi-weave provides easy cable installation •
- UL, CE certified



Classification	
Material Code	6004445
Part Number	DCG2429
Status	Active
Detail Description	Strain relief grip, deluxe cord, NPT 3", straight male, cable range 1.687-1.812"
Details	
Cable Range	1.687-1.812 in   42.85 -46.02 mm
Thread Size	NPT 3"
Mesh Length	15.0 in   381.0 mm
Mesh Material	Stainless Steel
Body Material	Aluminum
Performance	
Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting
Package	
Packaging Quantity	1 pcs
Weight, gross	2.315 lb   1.05 kg
Certifications	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant
CE	Compliant

For more information, please visit: www.maxdao.com

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 27, 2023 Public

