

**Strain Relief Grip, Deluxe Cord, NPT 3", Straight Male, Cable Range 1.812-1.937"**

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL, CE certified

**Classification**

Material Code	6004446
Part Number	DCG2431
Status	Active
Detail Description	Strain relief grip, deluxe cord, NPT 3", straight male, cable range 1.812-1.937"

**Details**

Cable Range	1.812-1.937 in   46.02 -49.20 mm
Thread Size	NPT 3"
Mesh Length	15.0 in   381.0 mm
Mesh Material	Stainless Steel
Body Material	Aluminum

**Performance**

Flammability	UL 94HB & UL 94V-2
Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting

**Package**

Packaging Quantity	1 pcs
Weight, gross	2.270 lb   1.03 kg

**Certifications**

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant

