


## Strain Relief Grip, Deluxe Cord, NPT 3/8", Straight Male, Cable Range 0.312-0.375"

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- **UL, CE certified**



| Classification         |   |
|------------------------|---|
|                        |   |
| Part Number            | DCG306  |
| Status                 | Active  |
| Detail Description     | Strain relief grip, deluxe cord, NPT 3/8", straight male, cable range 0.312-0.375"                          |
| Details                |   |
| Cable Range            | 0.312-0.375 in   7.92-9.53 mm   |
| Thread Size            | NPT 3/8"  |
| Mesh Length            | 3.60 in   91.4 mm   |
| Mesh Material          | Stainless Steel   |
| Body Material          | Aluminum  |
| Performance            |   |
| Flammability           | UL 94HB & UL 94V-2  |
| Hazardous Locations    | Suitable for use in hazardous locations per Class I, Div. 2 Class II, Div. 1 & 2; and Class III, Div. 1 & 2 |
| Operating Temperatures | -34 °C to +115 °C (-30 °F to +240 °F)   |
| Wet Locations          | Suitable for use in wet locations when used with a listed sealing ring between box and fitting              |
| Package                |   |
| Packaging Quantity     | 1 pcs   |
| Weight, gross          | 0.062 lb   0.028 kg   |
| Certifications         |   |
| ISO 9001:2015          | Designed, manufactured and/or distributed under this quality management system                              |
| RoHS                   | Compliant   |
| UL                     | Compliant   |
|                        |   |

For more information, please visit: www.maxdao.com







CE Compliant