

Cold Shrink End Cap, ϕ 35x75mm, EPDM, Black

- Made of EPDM rubber
- Simple and fast installation, no tools required
- No mastic or tape required
- Resists water, alkalis, acids, abrasion and ozone
- Easy removal



Product Classification

Item Number	TBD24
Part Number	-
Detail Description	Cold shrink end cap, ϕ 35x75mm, EPDM, Black

General Specifications

Material	EPDM
Cable Range	Φ 15.9-30.1 mm 0.63-1.18 in
Color	Black
Mastic(Y/N)	N

Dimensions

Inner Diameter Before Shrink(ID)	35 mm 1.38 in
Inner Diameter After Shrink(ID)	\leq 15.9 mm 0.63 in
Length Before Shrink	70 mm 2.75 in
Length After Shrink	75 mm 2.95 in
Thickness After Shrink	3.5 mm 0.137 in

Environmental Specifications

Operating Temperature	-40 °C to +90 °C (-40 °F to +194 °F)
Storage Temperature	-10 °C to +80 °C (14 °F to +176 °F)
Weatherproof Resistance	IP67, based on ISO20653:2013
UV Resistance	\geq 1000 hours, base on ASTM G154-16

Packaging and Weights

Height, Packed	200 mm 7.87 in
Width, Packed	200 mm 7.87 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.035 kg 0.086 lbs

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

