## # ITM0401 VERSION A/8 DATE 08/20/2024



## Cold Shrink End Cap, φ55x82mm, EPDM, Black

- Made of EPDM rubber
- Simple and fast installation, no tools required
- No mastic or tape required
- Resists water, alkalis, acids, abrasion and ozone
- Easy removal



Product Classification	
Item Number	TBD25
Part Number	-
Detail Description	Cold shrink end cap, ф55x82mm, EPDM, Black
General Specifications	
Material	EPDM
Cable Range	Ф26.0-49.2 mm   1.02-1.94 in
Color	Black
Mastic(Y/N)	N
Dimensions	
nner Diameter Before Shrink(ID)	55 mm   2.16 in
nner Diameter After Shrink(ID)	≤ 26 mm   1.02 in
ength Before Shrink	75 mm   2.95 in
Length After Shrink	82 mm   3.23 in
Thickness After Shrink	3.5 mm   0.137 in
nvironmental Specifications	
Operating Temperature	-40 °C to +90 °C (-40 °F to +194 °F)
Storage Temperature	-10 °C to +80 °C (14 °F to +176 °F)
Weatherproof Resistance	IP67, based on ISO20653:2013
JV Resistance	≥ 1000 hours, base on ASTM G154-16
Packaging and Weights	
Height, Packed	200 mm   7.87 in
Width, Packed	200 mm   7.87 in
JOM	1 Pcs
Packaging	Bag
Weight, Gross	0.070 kg   0.154 lbs







Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant



www.maxdao.com

For more information, please visit: