ΜΑΧΟΔΟ

Cold Shrink End Cap, φ90x100mm, EPDM, Black

- Made of EPDM rubber •
- Simple and fast installation, no tools required •
- No mastic or tape required •
- Resists water, alkalis, acids, abrasion and ozone •
- Easy removal



Product Classification	
Item Number	TBD26
Part Number	-
Detail Description	Cold shrink end cap, ф90х100mm, EPDM, Black
General Specifications	
Material	EPDM
Cable Range	Ф45.5-84.3 mm 1.79-3.32 in
Color	Black
Mastic(Y/N)	Ν
Dimensions	
Inner Diameter Before Shrink(ID)	90 mm 3.54 in
Inner Diameter After Shrink(ID)	≤ 45.5 mm 1.79 in
Length Before Shrink	90 mm 3.54 in
Length After Shrink	100 mm 3.94 in
Thickness After Shrink	3.5 mm 0.137 in
Environmental Specifications	
Operating Temperature	-40 °C to +90 °C (-40 °F to +194 °F)
Storage Temperature	-10 °C to +80 °C (14 °F to +176 °F)
Weatherproof Resistance	IP67, based on ISO20653:2013
UV Resistance	\geqslant 1000 hours, base on ASTM G154-16
Packaging and Weights	
Height, Packed	200 mm 7.87 in
Width, Packed	200 mm 7.87 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.154 kg 0.340 lbs

For more information, please visit:

©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Jan 9, 2025 Public



www.maxdao.com

Page 1 of 2



Certifications and Compliance

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

RoHS

Compliant

For more information, please visit: www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Jan 9, 2025 Public

Page 2 of 2