1 ATF# ITM0401 VFRSION A/8 DATE 08/20/202



Cold Shrink End Cap, φ120x100mm, EPDM, Black

- Made of EPDM rubber
- Simple and fast installation, no tools required
- No mastic or tape required
- Resists water, alkalis, acids, abrasion and ozone
- Easy removal



Product Classification	
Item Number	TBD27
Part Number	-
Detail Description	Cold shrink end cap, ф120x100mm, EPDM, Black
General Specifications	
Material	EPDM
Cable Range	Ф60.0-115.0 mm 2.36-4.53 in
Color	Black
Mastic(Y/N)	N
Dimensions	
Inner Diameter Before Shrink(ID)	120 mm 4.72 in
Inner Diameter After Shrink(ID)	≤ 60.0 mm 2.36 in
Length Before Shrink	90 mm 3.54 in
Length After Shrink	100 mm 3.94 in
Thickness After Shrink	3.5 mm 0.137 in
Environmental Specifications	
Operating Temperature	-40 °C to +90 °C (-40 °F to +194 °F)
Storage Temperature	-10 °C to +80 °C (14 °F to +176 °F)
Weatherproof Resistance	IP67, based on ISO20653:2013
UV Resistance	≥ 1000 hours, base on ASTM G154-16
Packaging and Weights	
Height, Packed	200 mm 7.87 in
Width, Packed	200 mm 7.87 in
UOM	1 Pcs
Packaging	Bag
Weight, Gross	0.206 kg 0.454 lbs

For more information, please visit: www.maxdao.com







Certifications and Compliance	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant



www.maxdao.com

For more information, please visit: