

## Strain Relief Grip, Deluxe Cord,PG36,Straight Male,Cable Range 0.88-1.00 in, SS304

- For indoor and outdoor where cables or wires are exposed to moisture or are frequently washed.
- Prevents severe cord bending and pull-out.
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- Multi-weave provides easy cable installation
- UL, CE certified



### Product Classification

Material Number	6007981
Part Number	-
Detail Description	Strain Relief Grip, Deluxe Cord,PG36,Straight Male,Cable Range 0.88-1.00 in, SS304

### Details

Cable Range	0.88-1.00 in   22.4-25.4 mm
Thread Size	PG36
Mesh Length	8.5 in   209.5 mm
Approximate Break Strength	450 lbs   204 kg
Mesh Material	Stainless Steel
Ring Material	Aluminum Alloy

### Performance

Flammability	UL 94HB & UL 94V-2
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting

### Packaging and Weights

UOM	1 pcs
Packaging	Bag
Weight, gross	0.66 lb   0.30 kg

### Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Maxdao Inc. All rights reserved.  
 The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.  
 Revised: Aug 30, 2024  
 Public

CE

Compliant

UL

Compliant

