

Liquidtight Conduit Connector, NPT 1-1/2", 90° angle

- For use in outdoor or indoor locations on flexible metallic liquid tight conduit and flexible nonmetallic liquid tight conduit to positively bond the conduit to a box or enclosure
- Liquid tight, rain tight, oil tight for protection and long life in wet, dusty environments
- Suitable for wet location use
- Insulated throat protects conductors from abrasion damage
- CE certified




Product Classification

Item Number	6009279
Part Number	-
Detail Description	Liquidtight Conduit Connector, NPT 1-1/2", 90° angle

General Specifications

Trade Size	NPT1-1/2"
Body Material	Zinc Plated Malleable Iron
Compression Nut Material	Zinc plated steel
Non-metallic Material	Nylon

Dimensions



Dimension A	4.13 in 105.0 mm
Dimension B	3.74 in 95.0 mm

Performance

Hazardous Locations	Suitable for use in hazardous locations per Class I, Div. 2; Class II, Div. 1 & 2; and Class III, Div. 1 & 2
---------------------	--

Package

UOM	1 pcs
Packaging	Carton
Weight, gross	0.88 lb 0.4 kg

Certifications and Compliance

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 30, 2024
Public

ISO 9001:2015

Designed, manufactured and/or distributed under this quality management system

RoHS

Compliant

CE

Compliant

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 30, 2024

Public