

Strain Relief Grip, Deluxe Cord, NPT 1/2", 90°Male, Cable Range 0.187-0.250"

- For use in indoor & outdoor applications to • prevent cable pull-out, control arc of bend, and to provide a tight seal against environmental elements such as dirt, moisture and coolants.
- Helps eliminate direct tension from terminals and • remove strain from critical electrical connection
- Multi-weave provides easy cable installation •
- UL, CE certified •

Classification	
Material Code	6004432
Part Number	-
Status	Active
Detail Description	Strain relief grip, deluxe cord, NPT 1/2", 90° male, cable range 0.187-0.250"
Details	
Cable Range	0.187-0.250 in 4.75-6.35 mm
Thread Size	NPT 1/2"
Mesh Length	4.25 in 107.8 mm
Mesh Material	Stainless Steel
Body Material	Aluminum
Performance	
Flammability	UL 94HB & UL 94V-2 (Fitting)
Operating Temperatures	-34 °C to +115 °C (-30 °F to +240 °F)
Wet Locations	Suitable for use in wet locations when used with a listed sealing ring between box and fitting
Package	
Packaging Quantity	1 pcs
Weight, gross	0.101 lb 0.046 kg
Certifications	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant

For more information, please visit: www.maxdao.com

©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 21, 2023

in \bowtie



Public

Page 1 of 2

DATASHEET

CE

Compliant



For more information, please visit: www.maxdao.com

in

©Copyright 2023 Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Feb 21, 2023 Public

 \square

Page 2 of 2