

## Strain Relief Grip, Dust Tight, NPT 1/2", Non-Insulated, Cable Range 0.30-0.43"

- For indoor use in wiring of enclosures, power boxes, machine tools, power centers and bus drop systems
- Prevents severe cable bending and pull-out
- Helps eliminate direct tension from terminals and remove strain from critical electrical connection
- **Easy installation**
- **UL, CE certified**



| Classification         |   |
|------------------------|---|
| Material Number        | 6002077   |
| Part Number            | -   |
| Status                 | Active  |
| Detail Description     | Strain relief grip, dust tight, NPT 1/2", cable range 0.30-0.43", with lock nut |
| Details                |   |
| Cable Range            | 0.30-0.43 in   7.62 -10.92 mm   |
| Thread Size            | NPT 1/2"  |
| Mesh Length            | 4.5 in   114.3 mm   |
| Approx. Break Strength | 300 lbs   136.1 kg  |
| Mesh Material          | Galvanized Steel  |
| Body Material          | Aluminum  |
| Performance            |   |
| Flammability           | UL 94HB & UL 94V-2  |
| Package                |   |
| Packaging Quantity     | 1 kit   |
| Weight, gross          | 0.057 lb   0.026 kg   |
| Certifications         |   |
| ISO 9001:2015          | Designed, manufactured and/or distributed under this quality management system  |
| RoHS                   | Compliant   |
| UL                     | Compliant   |
| CE                     | Compliant   |



