

Liquid tight Conduit Connector, Malleable Iron, NPT 1-1/2", Straight Male, Insulated

- Be Used When Liquid tight Conduit is in Tough, Industrial and Corrosive Applications
- Liquid tight, Rain tight, Oil tight for Protection and Long Life in Wet, Dusty and Corrosive Environments
- Hex Shaped Gland Nut Allows for Easy Wrenching, Providing a Fast, Tight Installation
- Reusable, Long Ferrule Prevents Pull-Out and Tight Bend Conduit Pop-Out
- Furnished with Lock nut and Sealing Ring
- UL, CE certified




Classification

Material Number	6007075
Part Number	-
Status	Active
Detail Description	Liquid tight conduit connector, malleable iron, NPT 1-1/2", straight male, insulated

General Specifications

Trade Size	NPT1-1/2"
Body Material	Zinc Plated Malleable Iron
Compression Nut Material	Zinc plated steel
Non-metallic Material	Nylon

Dimensions



Dimension A	1.37 in 34.8 mm
Dimension B	0.70 in 18.0 mm
Dimension C	2.36 in 60.0 mm

Package

UOM	1 pcs
Packaging	Carton
Weight, gross	0.571 lb 0.259 kg

Certifications

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
---------------	--



DATASHEET

RoHS	Compliant
UL	Compliant
CE	Compliant

For more information, please visit:
www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar 31, 2023

Public