

## Liquid tight Conduit Connector, Malleable Iron, NPT 1/2", Straight Male, Insulated

- Be Used When Liquid tight Conduit is in Tough, • **Industrial and Corrosive Applications**
- Liquid tight, Rain tight, Oil tight for Protection and • Long Life in Wet, Dusty and Corrosive Environments
- Hex Shaped Gland Nut Allows for Easy Wrenching, • **Providing a Fast, Tight Installation**
- Reusable, Long Ferrule Prevents Pull-Out and Tight • **Bend Conduit Pop-Out**
- Furnished with Lock nut and Sealing Ring
- UL, CE certified •



Classification	
Material Number	6007071
Part Number	-
Status	Active
Detail Description	Liquid tight conduit connector, malleable iron, NPT 1/2", straight male, insulated
General Specifications	
Trade Size	NPT1/2"
Body Material	Zinc Plated Malleable Iron
Compression Nut Material	Zinc plated steel
Non-metallic Material	Nylon
Dimensions	
Dimension A	1.00 in   25.4 mm
Dimension B	0.55 in   14.0 mm
Dimension C	1.25 in   31.8 mm
Package	
UOM	1 pcs
Packaging	Carton
Weight, gross	0.139 lb   0.063 kg
Certifications	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
	dao Inc. All rights reserved. Page 1 of 2

We reserve the right to ma changes or modify the contents of this document without prior notice. Revised: Mar 31, 2023 Public



UL CE



Compliant

Compliant

For more information, please visit: www.maxdao.com



©**Copyright 2023 Maxdao Inc. All rights reserved.** The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Mar 31, 2023 Public

Page 2 of 2