

Liquid tight Conduit Connector, Malleable Iron, NPT 1", Straight Male, Insulated


- Be Used When Liquid tight Conduit is in Tough, Industrial and Corrosive Applications
- Liquid tight, Rain tight, Oil tight for Protection and Long Life in Wet, Dusty and Corrosive Environments
- Hex Shaped Gland Nut Allows for Easy Wrenching, Providing a Fast, Tight Installation
- Reusable, Long Ferrule Prevents Pull-Out and Tight Bend Conduit Pop-Out
- Furnished with Locknut and Sealing Ring
- UL, CE certified

**Classification**

| | |
|--------------------|--|
| Material Number | 6007073 |
| Part Number | - |
| Status | Active |
| Detail Description | Liquid tight conduit connector, malleable iron, NPT 1", straight male, insulated |

General Specifications

| | |
|--------------------------|----------------------------|
| Trade Size | NPT1" |
| Body Material | Zinc Plated Malleable Iron |
| Compression Nut Material | Zinc plated steel |
| Non-metallic Material | Nylon |

Dimensions

| | |
|-------------|-------------------|
| Dimension A | 1.13 in 28.7 mm |
| Dimension B | 0.63 in 16.0 mm |
| Dimension C | 1.76 in 44.8 mm |

Package

| | |
|---------------|---------------------|
| UOM | 1 pcs |
| Packaging | Carton |
| Weight, gross | 0.319 lb 0.145 kg |

Certifications

| | |
|---------------|--|
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |

UL

Compliant

CE

Compliant

