

## Liquid tight Conduit Connector, Malleable Iron, NPT 3/4", Straight Male, Insulated

- Be Used When Liquid tight Conduit is in Tough, Industrial and Corrosive Applications
- Liquid tight, Rain tight, Oil tight for Protection and Long Life in Wet, Dusty and Corrosive Environments
- Hex Shaped Gland Nut Allows for Easy Wrenching, Providing a Fast, Tight Installation
- Reusable, Long Ferrule Prevents Pull-Out and Tight Bend Conduit Pop-Out
- Furnished with Lock nut and Sealing Ring
- UL, CE certified




### Classification

Material Number	6007072
Part Number	-
Status	Active
Detail Description	Liquid tight conduit connector, malleable iron, NPT 3/4", straight male, insulated

### General Specifications

Trade Size	NPT3/4"
Body Material	Zinc Plated Malleable Iron
Compression Nut Material	Zinc plated steel
Non-metallic Material	Nylon

### Dimensions



Dimension A	1.00 in   25.4 mm
Dimension B	0.60 in   14.0 mm
Dimension C	1.43 in   36.2 mm

### Package

UOM	1 pcs
Packaging	Carton
Weight, gross	0.198 lb   0.090 kg

### Certifications

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

For more information, please visit:  
[www.maxdao.com](http://www.maxdao.com)



©Copyright 2023 Maxdao Inc. All rights reserved.  
 The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.  
 Revised: Mar 31, 2023  
 Public

UL

Compliant

CE

Compliant

