

Liquid tight Conduit Connector, Malleable Iron, NPT 1", 45 Degree Male, Insulated

- Be Used When Liquid tight Conduit is in Tough, Industrial and Corrosive Applications
- Liquid tight, Rain tight, Oil tight for Protection and Long Life in Wet, Dusty and Corrosive Environments
- Hex Shaped Gland Nut Allows for Easy Wrenching, Providing a Fast, Tight Installation
- Reusable, Long Ferrule Prevents Pull-Out and Tight Bend Conduit Pop-Out
- Furnished with Lock nut and Sealing Ring
- UL, CE certified



Classification	
Material Number	6007079
Part Number	-
Status	Active
Detail Description	Liquid tight conduit connector, malleable iron, NPT 1", 45 degree male, insulated
General Specifications	
Trade Size	NPT1"
Body Material	Zinc Plated Malleable Iron
Compression Nut Material	Zinc plated steel
Non-metallic Material	Nylon
Dimensions	
Dimension A	2.50 in 63.5 mm
Dimension B	0.70 in 17.8 mm
Dimension C	1.76 in 44.7 mm
Package	
UOM	1 pcs
Packaging	Carton
Weight, gross	0.493 lb 0.223 kg
Certifications	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system

For more information, please visit: www.maxdao.com

in

 \times

©Copyright 2023 Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Mar 31, 2023 Public

DATASHEET

RoHS	Compliant
UL	Compliant
CE	Compliant

TEMPLATE# ITM-04-01 VERSION A/4 DATE 03/25/2023

For more information, please visit: www.maxdao.com



©Copyright 2023 Maxdao Inc. All rights reserved. The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice. Revised: Mar 31, 2023 Public

Page 2 of 2

MAXDAO