TEMPLATE# ITM0401 VERSION A/8 DATE 08/20/2024



Acetal Banding, 1/2"x50'/reel, Black

- Weatherproof acetal strap on reel
- Used with acetal double locking head
- Excellent resistance to ultraviolet light and chemicals
- Meets Telcordia TR-TSY-000789



| Product Classification | |
|-------------------------------|------------------------------------------------------|
| Item Number | 6002821 |
| Part Number | - |
| Detail Description | Acetal Banding, 1/2"x50feet/reel, Black |
| General Specifications | |
| | Acetal plastic |
| Color | Black |
| Dimensions | |
| Width | 12.5 mm 0.49 in |
| Length | 15 m 50 feet |
| Thickness | 1.5 mm 0.06 in |
| Mechanical Specifications | |
| Minimum loop Tensile Strength | 1112 N 250 lbs |
| Environmental Specifications | |
| Operating Temperature | -40 °C to +85 °C (-40 °F to +185 °F) |
| Flammability | UL94 HB |
| UV Resistance | ≥1000 hours, base on ISO4892.3-1994 |
| Packaging and Weights | |
| Height, Packed | 300 mm 11.81 in |
| | 300 mm 11.81 in |
| UOM | Pcs |
| Packaging | Bag |
| Weight, Gross | 0.444 kg 0.978 lbs |
| Certifications and Compliance | |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this |
| | |

For more information, please visit: www.maxdao.com







| | quality management system |
|---------------|---------------------------|
| RoHS | Compliant |
| TR-TSY-000789 | Qualified |