


Grounding Kit, GST Type, 1-1/4", 1.5 Meter

- Easy and quick installation
- Low contact transition resistance of maximum 10mΩ
- Operation temperature -40~70 °C
- Waterproof IP68

**Product Classification**

Item Number	6009254
Part Number	-
Detail Description	Grounding kit, GST type, for 1-1/4" cable, 1.5 meter, installation accessories included

General Specifications

Bonding Conductor Material	Copper
Bonding Conductor Wire Size	AWG 6
Grounding Strap Material	Copper
Lug Type	Two-hole lug
Screw Material	Stainless Steel
Flat washer Material	Stainless Steel
Spring washer Material	Stainless Steel
Nut Material	Stainless Steel
PVC tape Material	PVC
Butyl Rubber Tape Material	Butyl

Dimensions

Bonding Conductor Length	1.5 m 5 feet
Lug Hole Size	3/8"
Screw Size	3/8"x1"
Suitable Cable	1-1/4"

Environmental Specifications

Operating Temperature	-40°C to +70 °C (-40 °F to +158 °F)
Weatherproofing Method	Butyl and electric tape

Electrical Specifications

Contact Transition Resistance	Maximum 10mΩ
-------------------------------	--------------

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Mar. 6, 2025
 Public

Packaging and Weights

Height, Packed	320 mm 12.60 in
Width, Packed	220 mm 8.66 in
Included	Grounding kit Hardware Lug One roll of PVC tape One roll of butyl rubber tape Installation guide
UOM	Kit
Packaging	Bag
Weight, Gross	0.53 kg 1.17 lbs

Certifications and Compliance

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant

