## ΜΑΧΡΔΟ


## Copper Lug, AWG4#, one hole 3/8", standard barrel, with inspection window, gray


- Copper cable lugs are designed for connecting copper cables, coils and Bus-bars.
- Copper Tube Terminals between 6mm<sup>2</sup> & 800mm<sup>2</sup> have bell entry to ensure easy entry even for flexible conductors.
- Incorporates inspection window to check the correct cable positioning.
- The barrel length has been designed to allow easy and accurate positioning of the dies during the crimping operation.
- "colour code" help choose the right connector, the colour name is also printed in order to avoid problems for those who are colour-blind.



Product Classification	
Item Number	6009307
Part Number	-
Detail Description	Copper Lug,AWG4#,one hole 3/8",standard barrel,with inspection window,gray
General Specifications	
Colour	Gray
Material	Copper
Tongue Type	Standard
Tongue Angle	Straight
Surface	Tin-plated
Inspection Window	With inspection window

## **Dimensions**





Rating - Maximum Voltage	35KV
Detice Manter of Malkers	25107
Electrical Specifications	
Outer diameter (OD)	0.38 in   9.7 mm
Inner diameter (ID)	0.28 in   7.2 mm
Overall length (L)	1.92 in   48.7 mm
Barrel length (B)	0.81 in   20.6 mm
Tang Width (C)	0.58 in   14.7 mm
Bolt Size	3/8 in   10.2 mm

## **Environmental Specifications**

TEMPLATE# ITM0401 VERSION A/8 DATE 08/20/2024





Operating Temperature	-40 °C to +90°C (-40 °F to +212 °F)
Storage Temperature	-40 °C to +80 °C (-40 °F to +176 °F)
Packaging and Weights	
Included	Lug
Packaging Quantity and UOM	1 pcs
Piece Weight	0.037 lb   0.017 kg
Certifications and Certificated	
ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
RoHS	Compliant
UL	Compliant