

Cold Shrink Tube, ϕ 40x125mm, Red

- Easy and quick installation
- Manufactured from silicone rubber
- Suitable for a wide range of cable sizes
- No special tools or training required for installation
- Offering good mechanical, insulation and sealing protection



Product Classification

Item Number	6009329
Part Number	-
Detail Description	Cold shrink tube, ϕ 40x125mm, red

General Specifications

Material	Silicone
Cable type	Corrugated Elliptical Waveguide Smoothwall
Cable Range	ϕ 12-35 mm 0.47-1.37 in
Color	Red
Mastic(Y/N)	N
Shrink Ratio	4:1

Dimensions

Length Before Shrink	125 mm 4.92 in
Length After Shrink	150 mm 5.91 in
Inner Diameter Before Shrink(ID)	40 mm 1.57 in
Inner Diameter After Shrink(ID)	10 mm 0.39 in
Thickness After Shrink	3.1 mm 0.12 in

Environmental Specifications

Operating Temperature	-60 °C to +90 °C (-76 °F to +194 °F)
Weatherproof Resistance	IP67, based on ISO20653:2013
UV Resistance	\geq 1000 hours, base on ASTM G154-16

Packaging and Weights

Height, Packed	260 mm 10.23 in
Width, Packed	70 mm 2.75 in
UOM	1 Pcs
Packaging	Bag

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Aug 8, 2024
Public

Weight, Gross	0.061 kg 0.134 lbs
---------------	----------------------

Certifications and Compliance	
--------------------------------------	--

ISO 9001:2015	Designed, manufactured and/or distributed under this quality management system
---------------	--

RoHS	Compliant
------	-----------

