

Hook Cable Clamp, M Type, 4x5-7mm+3x7-22mm

- Easy and quick installation
- Robust design & material for outdoor use
- Operation Temperature -40~85 °C
- Hooking on round \varnothing 8-25 and flat 3-25 mm



Product Classification

| | |
|--------------------|---|
| Item Number | 6009331 |
| Part Number | - |
| Detail Description | Hook Cable Clamp for 4x5-7mm+3x7-22mm cable, hooking on round \varnothing 8-25 and flat 3-25 mm |

General Specifications

| | |
|-------------------|------------------------|
| Metal Material | Stainless steel 304 |
| Block Material | PA6 |
| Block Color | Black |
| Cables Per Hanger | 4 X 5-7 mm+3 X 7-22 mm |

Dimensions

| | |
|---------------------------------------|---------------------|
| Height | 270.0 mm 10.63 in |
| Width | 30.4 mm 1.20 in |
| Length | 41.5 mm 1.63 in |
| Compatible Cable 1 Jacket OD, maximum | 7.0 mm 0.275 in |
| Compatible Cable 1 Jacket OD, minimum | 5.0 mm 0.197 in |
| Compatible Cable 2 Jacket OD, maximum | 22.0 mm 0.866 in |
| Compatible Cable 2 Jacket OD, minimum | 7.0 mm 0.275 in |

Environmental Specifications

| | |
|-----------------------|--|
| Operating Temperature | -40 °C to +85 °C (-40 °F to +185 °F) |
| Corrosion Resistance | ≥96 hours in salt spray chamber, base on ISO 9227:2017 |
| UV Resistance | ≥720 hours, base on ISO4892.3-1994 |
| Vibration Test | ≥6 Hours, base on IEC 60068-2-6-2007 |

Packaging and Weights

| | |
|----------------|-------------------|
| Height, Packed | 320 mm 12.60 in |
| Width, Packed | 220 mm 8.66 in |

For more information, please visit:
www.maxdao.com



©Maxdao Inc. All rights reserved.

The information contained herein is subject to change without notice. We reserve the right to make technical changes or modify the contents of this document without prior notice.

Revised: Sep 18, 2024

Public

| | |
|--------------------------------------|--|
| UOM | 1 Pcs |
| Packaging | Bag |
| Weight, Gross | 0.224 kg 0.493 lbs |
| Certifications and Compliance | |
| ISO 9001:2015 | Designed, manufactured and/or distributed under this quality management system |
| RoHS | Compliant |

